

IP CAMERA 5MP MOTORRIZED LENS AUTO FOCUS, POE



W695GAHZ86A (Motorized Lens)

H.265 5MP 4X Zoom Motorized POE

Features:

- 1/2.8" Sony CMOS sensor
- 5MP realtime resolution 2560x1944P
- Low illumination 0.01Lux
- Day/Night, AWB/MWB,BLC, HLC, 2D/3D-DNR,Shutter, IR-CUT
- D-WDR,Mirror, rotate, Defogging
- Multiply Style OSD Overlay,Motion Detection, Privacy Mask
- RTSP and On-vif 17.06 compatible with many third-party NVR
- H.264/H.265 dual-stream media server
- Easy-to-use P2P Cloud service
- Support user authentication, video data encryption
- Support Alarm Snapshot to Email and FTP
- Multiply WEB browser IE,Firefox 32 bit ESR, PC Client, Mobile APP remote access
- RJ45 100mbps network port, IEEE802.3af PoE
- Lightning protection 4000V
- Strong water-proof housing, IP66
- 4pcs array IR Leds, IR distance 80 meters
- HD 2.8-12 mm motorized lens

Technical Specifications:

Model YC-W695GAHZ86A

Camera Image Sensor 1/2.8" Sony CMOS

Effective Pixels 5 megapixels

Electronic Shutter AUTO, 1/25s ~ 1/100000s

Min. Illumination 0.01Lux@F1.2(AGC ON), 0Lux IR on

Day/Night Auto/Color/(B/W)/Timing

WDR Digital WDR

White Balance Auto/Manual

BLC /HLC Support

DNR 2D/3D DNR

Other AGC, Motion Detection, Privacy Mask, Flip , OSD overlay

Encode Video Standard H.264/H.265

Video Resolution

Main Stream: 25fps@5MP(2592x1944)/4MP(2592x1520)/3MP, 30fps@1080P/720P

Sub stream: 25fps@D1/VGA/360P/CIF, etc.

Video Bitrates 512Kbps - 12Mbps, VBR/CBR

Audio Standard G.711-u/G.711-a

Built-in Mic Optional

OSD Overlay Title and Time overlay

IR Led

IR Led 4 pcs array IR Led

IR Distance 80M

Lens

Focal length 2.8-12 mm motorized lens

Optional Function PoE

Network Services

Protocol HTTP/RTSP/FTP/SMTP/DHCP/NTP/NFS, etc.

P2P Yes

Web IE , Firefox (32bit esr), etc.

Media CMS, Android, IOS

ON-VIF 17.06 compatible

General

Network Port 1-RJ45, 100Mbps, POE optional

Power Supply 12 VDC \pm 10%

Power Consumption < 8 W

Operating Temp. -30°C-(+60)°C, 10%-90%RH