

เครื่องบันทึก NVR จำนวน 32 ช่อง NVR6232G-V2



NVR6232G-V2เครื่องบันทึก HIKVISION NVR จำนวน 32 ช่อง

32CHs 8MP H.265/H.264 NVR

Features:

Support 32 CHs 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P IP input

Adopt standard H.265 and H.264 high profile compression format to get high-quality video at much lower bit rate

Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse

Multi-

mode recording: manual / timer / motion / sensor

Playback : 16 CHs simultaneous playback

Search : time slice, time, event (manual, sensor, motion), tag search

Express and flexible backup via USB, network and so on

Pentaplex : preview, record, playback, backup and remote access

DHCP, DDNS, PPPoE network protocol and CMS supported

Remote control via IE or CMS : preview, playback, backup, PTZ and configuration

Dual stream technology for local storage with high definition, remote network transmission

and remote surveillance with mobile device

user online simultaneously

Authorization management, log view and device status view

K output, true high resolution display

Support PTZ preset and auto cruise, up to 255 presets and 8 cruises

Support NAT function and QRCode scanning by mobile phone and PAD

Powerful smart phone & Pad surveillance with iOS and Andriod OS

Technical Specifications:

Model YCX-NVR6232G-V2

System

Compression Standard H.265
Main Processing Chip ARM Cortex A7
OS Embedded Linux

Video

Network Access Bandwidth 144Mbps
Input Resolution 8MP、5MP、4MP、3MP、1080P、960P、720P real time
Network Access 32 CH IPC input
Output HDMI×1 : 3840×2160/1920×1080/1280×1024/1024×768 VGA×1 :
1920×1080/1280×1024/1024×768

Audio

Input 32 CH IPC audio input
2-way Audio RCA×1
Local Output RCA×1

Record

Resolution 8MP、5MP、4MP、3MP、1080P、960P、720P
Frame Rate 25fps/30fps(PAL/NTSC)
Bite Stream 32Kbps-10Mbps
Image Quality 5 Level

Playback

Simultaneous Playback Max 16 CH

Network

Interface RJ45 10/100/1000 Mbps × 1
Network Protocol TCP/IP、PPPoE、DHCP、DNS、DDNS、UPnP、NTP、SMTP、
ONVIF、GB28181

Storage

HDD SATA×2
Max Capacity for 1 single HDD 8TB
Backup
USB Backup Yes
eSata Backup No

Interface

Alarm In 4
Alarm Output 1
Communication RS485 × 2, connect to PTZ and keyboard
Remote Optional
USB USB2.0×2 (one in the front panel and the other in the rear panel)

Others

Case 1U
Dimensions(mm) 380×268×52(W×D×H)
Power Supply DC12V
Consumption ≤ 15W (without HDD)
Work Environment -10 ~ 50 °C, 10% ~ 90% humidity