

IP CAMERA 5 MP W695AHBB94CA



W695AHBB94CA

5MP Fixed Mini Human body Detection Dome POE IP Camera

Features:

- 1/2.8" Sony CMOS sensor
- 5MP realtime resolution 2560x1944P
- Low illumination 0.01Lux
- Day/Night, AWB/MWB,BLC, HLC, 2D/3D-DNR,Shutter, IR-CUT
- D-WDR,Mirror, rotate, Defogging
- Multiply Style OSD Overlay,Motion Detection, Privacy Mask
- RTSP and On-vif 17.06 compatible with many third-party NVR
- H.264/H.265 dual-stream media server
- Easy-to-use P2P Cloud service
- Support user authentication, video data encryption
- Support Alarm Snapshot to Email and FTP
- Multiply WEB browser IE,Firefox 32bit ESR, PC Client, Mobile APP remote access
- RJ45 100mbps network port, IEEE802.3af PoE
- Lightning protection 4000V
- Strong water-proof housing, IP66
- 18 pcs SMD Array IR Leds, IR distance 30 meters
- HD 3.6 mm fixed lens

Technical Specifications:

Model YC-W695AHBB94CA

Camera

Image Sensor 1/2.8" Sony CMOS

Effective Pixels 5 megapixels

Electronic Shutter AUTO, 1/25s ~ 1/100000s

Min. Illumination 0.01Lux@F1.2(AGC ON), 0Lux IR on

Day/Night Auto/Color/(B/W)/Timing

WDR Digital WDR

White Balance Auto/Manual

BLC /HLC Support

DNR 2D/3D DNR

Other AGC,Motion Detection,Privacy Mask,Flip ,OSD overlay

Encode

Video Standard H.264/H.265

Video Resolution

Main Stream: 25fps@5MP(2592x1944)/4MP(2592x1520)/3MP, 30fps@1080P/720P

Sub stream 25fps@D1/VGA/360P/CIF, etc.

Video Bitrates 512Kbps - 12Mbps, VBR/CBR

Audio Standard G.711-u/G.711-a

Built-in Mic Optional

OSD Overlay Title and Time overlay

IR Led

IR Led 18 pcs IR Led

IR Distance 30M

Lens

Focal length 3.6 mm fixed lens

Optional Function PoE, audio

Network Services

Protocol HTTP/RTSP/FTP/SMTP/DHCP/NTP/NFS, etc.

P2P Yes

Web

IE , Firefox (32bit esr), etc.

Media CMS, Android, IOS

ON-VIF 17.06 compatible

General

Network Port 1-RJ45, 100Mbps, POE optional

Power Supply 12 VDC \pm 10%

Power Consumption < 8 W

Operating Temp. -30°C-(+60)°C, 10%-90%RH